



SAE 50

4 Stroke Engine Oil
For vintage cars and motorcycles

Mineral Monograde

TYPE OF USE

Especially formulated for collector and vintage cars engines and gearboxes built between 1900 and 1950.

Suitable for Gasoline or Diesel 4 stroke engines. Also suitable for collector bike engines.

PERFORMANCE

MOTUL SAE 50 is a last generation oil specially designed for old technology engines.

Mineral monograde lubricant with very low detergent level for a complete compatibility with paper ,felt and fabric gaskets.

Small detergent level avoids soot and deposits removing in the lubricating circuit.

Can be used as break-in oil if drain intervals are shortened.

Complete compatibility with nonferrous metals as brass, bronze, cooper.

Reinforced adherence for easier start even after a long period of immobilization.

RECOMMENDATIONS

Drain interval : drain at least once a year.

PROPERTIES

Viscosity grade	SAE J 300	50
Density at 20°C (68°F)	ASTM D1298	0.897
Viscosity at 40°C (104°F)	ASTM D445	256 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	21.3 mm ² /s
Viscosity index	ASTM D2270	98
Pour point	ASTM D97	-18°C / -0.4°F
Flash point	ASTM D92	281°C / 537.8°F
TBN	ASTM D2896	1.5 mg KOH/g